
SHAFTS SCREENERS


MB-HDS323







Α





SPECIFICATIONS



Recommended excavator	lb	48,500 - //,160
Recommended backhoe loader/loader*	lb	26,460 - 35,270
Weight		5,291
Load capacity	СУ	2.16
Pressure	PSI	3,626 - 4,351
Oil flow rate**	gal/min	32 - 42
Size A	in	92
Size B	in	59
Size C	in	49

^{*} Please verify machine's Rated Operating Capacity

SHAFT KIT

KIT

RM Mixer kit

RQ8 Sifting kit	
RQ20 Sifting kit	
RQ50 Sifting kit	

0.30 in	
0.8 in	
2.0 in	

ADJUSTMENT*

Sifting damp/dry soil Soil Aeration

APPLICATION



Sifting damp/dry soil

Soil Aeration





Shredding foliage and small branches Composting

OPTIONAL ACCESSORIES

RQ8 Sifting kit	RQ20 Sifting kit
RQ50 Sifting kit	RM Mixer kit
RE8 Fine sifting kit	RE16 Fine sifting kit
RC Compost kit	Shaft holder
24 Month warranty	

APPLICATION AREAS



Road works



oelines



Quarry



Recycling aggregates E







Enclosed space



Foundries



Maintaining landscape and agricultural areas

^{**} The minimum hydraulic flow rate value must be alongside the required operating pressure

^{*} Shafts in closed position.