

Drum











Lampade da parete-soffitto con diffusore in vetro opale satinato soffiato a bocca, e struttura in policarbonato anti UV traslucido neutro resistente al cloro (Drum) o con strutture in metallo verniciato bianco (Drum Bayonet). Entrambi i modelli hanno la chiusura del vetro a baionetta. Il prodotto è adatto esclusivamente all'uso interno. Il modello Drum ha un grado di protezione IP44 lo rende particolarmente indicato per piscine e ambienti umidi.





Wall-ceiling lamps with diffuser in mouth blown, satin-finish opal glass; frame in chlorine-resistant, anti-UV, neutral translucent polycarbonate (Drum) or in white painted metal (Drum Bayonet). Both models have a twist-lock coupling system for the glass component. The product is suitable for internal use only; although the model Drum has an IP44 rating that makes it ideal for use in swimming pools and humid environments in general.







Drum wall-ceiling lamp → **LD8761N3**





SPECIFICHE SPECIFICATIONS	DATI TECNICI TECHNICAL DATA	FINITURE FINISHES	CODICE CODE
parete-soffitto wall-ceiling  Ø 30 x 10 cm Ø 11,8 x 3,9 in	E27 220-240V 1x42W IP44	Trasparente / Clear	LL8701NE
	LED 220-240V 3000K CRI>90 12,5W 1350lm beam angle 127° IP44	Trasparente / Clear	LED 2700-4000K su richiesta / on request LD8701N3
	LED TRIAC  220-240V 3000K CRI>90 12,5W 1350lm beam angle 127° IP44	Trasparente / Clear	LD870113N3
	LED DALI  220-240V 3000K CRI>90 12,5W 1350lm beam angle 127° IP44	Trasparente / Clear	LD870123N3
	LED WI-FI  220-240V 3000K CRI>90 12,5W 1350lm beam angle 127° IP44	Trasparente / Clear	LD870133N3

parete-soffitto wall-ceiling  Ø 40 x 11 cm Ø 15,7 x 4,3 in	E27 220-240V 2x42W IP44	Trasparente / Clear	LL8731NE
	LED 220-240V 3000K CRI>90 19,5W 2100lm beam angle 122° IP44	Trasparente / Clear	LED 2700-4000K su richiesta / on request LD8731N3
	LED EMERGENCY (3h) 220-240V 3000K CRI>90 5-18,5W 2200lm beam angle 122° IP44	Trasparente / Clear	LD8742N3
	LED TRIAC  220-240V 3000K CRI>90 18,5W 2100lm beam angle 122° IP44	Trasparente / Clear	LD873113N3
	LED DALI  220-240V 3000K CRI>90 18,5W 2100lm beam angle 122° IP44	Trasparente / Clear	LD873123N3
LED WI-FI  220-240V 3000K CRI>90 18,5W 2100lm beam angle 122° IP44	Trasparente / Clear	LD873133N3	

SPECIFICHE SPECIFICATIONS	DATI TECNICI TECHNICAL DATA	FINITURE FINISHES	CODICE CODE
parete-soffitto wall-ceiling  Ø 50 x 12 cm Ø 19,7 x 4,7 in	E27 220-240V 3x42W IP44	Trasparente / Clear	LL8761NE
	LED 220-240V 3000K CRI>90 30W 3000lm beam angle 116° IP44	Trasparente / Clear	LED 2700-4000K su richiesta / on request LD8761N3
	LED EMERGENCY (3h) 220-240V 3000K CRI>90 5-29W 3000lm beam angle 116° IP44	Trasparente / Clear	LD8772N3
	LED TRIAC  220-240V 3000K CRI>90 29W 3000lm beam angle 116° IP44	Trasparente / Clear	LD876113N3
	LED DALI  220-240V 3000K CRI>90 29W 3000lm beam angle 116° IP44	Trasparente / Clear	LD876123N3
LED WI-FI  220-240V 3000K CRI>90 29W 3000lm beam angle 116° IP44	Trasparente / Clear	LD876133N3	

SPECIFICHE SPECIFICATIONS	DATI TECNICI TECHNICAL DATA	FINITURE FINISHES	CODICE CODE	
parete-soffitto wall-ceiling  Ø 30 x 10 cm Ø 11,8 x 3,9 in	E27 220-240V 1x52W IP20	Bianco / White	LL8910	
	LED 220-240V 3000K CRI>90 12,5W 1350lm beam angle 127° IP20	Bianco / White	LED 2700-4000K su richiesta / on request	LD891003
	LED TRIAC  220-240V 3000K CRI>90 12,5W 1350lm beam angle 127° IP20	Bianco / White		LD891013
	LED DALI  220-240V 3000K CRI>90 12,5W 1350lm beam angle 127° IP20	Bianco / White		LD891023
	LED WI-FI  220-240V 3000K CRI>90 12,5W 1350lm beam angle 127° IP20	Bianco / White		LD891033

parete-soffitto wall-ceiling  Ø 40 x 11 cm Ø 15,7 x 4,3 in	E27 220-240V 2x52W IP20	Bianco / White	LL8911	
	LED 220-240V 3000K CRI>90 19,5W 2100lm beam angle 122° IP20	Bianco / White	LED 2700-4000K su richiesta / on request	LD891103
	LED EMERGENCY (3h) 220-240V 3000K CRI>90 5-18,5W 2100lm beam angle 122° IP20	Bianco / White		LD894103
	LED TRIAC  220-240V 3000K CRI>90 18,5W 2100lm beam angle 122° IP20	Bianco / White		LD891113
	LED DALI  220-240V 3000K CRI>90 18,5W 2100lm beam angle 122° IP20	Bianco / White		LD891123
LED WI-FI  220-240V 3000K CRI>90 18,5W 2100lm beam angle 122° IP20	Bianco / White		LD891133	

SPECIFICHE SPECIFICATIONS	DATI TECNICI TECHNICAL DATA	FINITURE FINISHES	CODICE CODE	
parete-soffitto wall-ceiling  Ø 50 x 12 cm Ø 19,7 x 4,7 in	E27 220-240V 3x52W IP20	Bianco / White	LL8912	
	LED 220-240V 3000K CRI>90 30W 3000lm beam angle 116° IP20	Bianco / White	LED 2700-4000K su richiesta / on request	LD891203
	LED EMERGENCY (3h) 220-240V 3000K CRI>90 5-29W 3000lm beam angle 116° IP20	Bianco / White		LD894203
	LED TRIAC  220-240V 3000K CRI>90 29W 3000lm beam angle 116° IP20	Bianco / White		LD891213
	LED DALI  220-240V 3000K CRI>90 29W 3000lm beam angle 116° IP20	Bianco / White		LD891223
LED WI-FI  220-240V 3000K CRI>90 29W 3000lm beam angle 116° IP20	Bianco / White		LD891233	