

Aleasol RAPID

COMPOSITION

E224 Potassium Metabisulfite (60%), Ammonium Phosphate Bibasic (22%), Ammonium Sulfate (18%).

GENERAL CHARACTERISTICS

Appearance: homogeneous white powder, with an odor of $_{\rm SO2}$

ALEASOL RAPID acts as a regulator of fermentation, enhancing the action of selected yeasts and inhibiting wild yeasts. The antimicrobial action of metabisulfite and proper yeast nutrition provided by ammonium salts prevent any fermentation arrests.

APPLICATIONS

The use of ALEASOL RAPID is particularly recommended if the phytosanitary state of the grapes is not optimal.

RECOMMENDED DOSAGES

10 to 25 g/hl, depending on the phytosanitary state of the grapes.
Take care not to exceed the legal limits for sulfur dioxide content.
Current EU regulations specify the following limits, expressed as total SO2:

(a) 160 mg/l for red wines;
(b) 210 mg/l for white and rosé wines;
(c) 185 mg/l for quality sparkling wines and VSQPRDs
(d) 235 mg/l for sparkling wines.

For non-sparkling wines with residual sugar content, expressed as invert sugar, of 5 g/l or more, the limits become as follows:

(a) 210 mg/l for red wines;

(b) 260 g/l for white and rosé wines.

1 g of ALEASOL RAPID provides approximately 3 mg/l of SO2.

MODE OF USE

Dissolve **ALEASOL RAPID** in water, at a ratio of 1:10, then add it into the mass to be treated, homogenizing thoroughly.

PACKAGES AVAILABLE

200 g bag

STORAGE CONDITIONS

Unopened package: store in a cool (temperature below 25°C), dry and ventilated place.

Open package: close tightly and store as indicated above.

WARNING: Aleasol RAPID Afraid of moisture.

Exclusively for oenological and professional use - Reg. (EU) 2022/68 Product obtained from raw materials in accordance with O.I.V. International Oenological Codex Contains allergens: SO2

40062 Molinella (BO) - ITALIA Tel. +39 051 88 7052 +39 346 58 33 882 info@alea-evolution.com alea-evolution@pec.it alea-evolution.com CF - P.IVA 02944251202 Cod. REA BO-479327 Capitale sociale € 40.000,00 i.v.

Via Sandro Pertini, 12



The information given in this Technical Data Sheet corresponds to the current state of our knowledge and is subject to modification and supplementation without prior notice. The methods of use given do not relieve the user from the application and observance of safety and protection regulations. Adaptation to individual cases, as a consequence of the specific circumstances of each use, as well as possible misuse of the product, do not involve the responsibility of Alea Evolution S.R.L.