
SHAFTS SCREENERS

MB-HDS323





A





SPECIFICATIONS



Recommended excavator	lb	48,500 - 77,160
Recommended backhoe loader/loader*	lb	26,460 - 35,270
Weight	lb	5,291
Load capacity	СУ	2.16 - 2.62**
Load capacity with coal capacity increase kit	СУ	2.62 - 3.14**
Pressure	PSI	3,626 - 4,351
Oil flow rate***	gal/min	32 - 42
Size A	in	92
Size B	in	59
Size C	in	49
•		

^{*} Please verify machine's Rated Operating Capacity

SHAFT KIT

KIT	ADJUSTMENT*	APPLICATION
RQ8 Sifting kit RQ20 Sifting kit RQ50 Sifting kit	0.30 in 0.8 in 2.0 in	Sifting damp/dry soil Soil Aeration
RM Mixer kit		Soil Aeration Compost Aeration Charcoal reduction Glass reduction Drywall reduction
RE8 Fine sifting kit RE16 Fine sifting kit	0.30 in 0.60 in	Sifting damp/dry soil
RC Compost kit	1.40 in	Shredding foliage and small branches Composting

^{*} Shafts in closed position.

OPTIONAL ACCESSORIES

RQ8 Sifting kit	RQ20 Sifting kit
RQ50 Sifting kit	RM Mixer kit
RE8 Fine sifting kit	RE16 Fine sifting kit
RC Compost kit	Shaft holder

APPLICATION AREAS









Inert material recycling







Urban construction site



Foundries



Maintaining landscape and agricultural areas

^{**} The value of the load capacity varies according to the type of material being processed.

^{***} The minimum hydraulic flow rate value must be alongside the required operating pressure