



SHAFTS SCREENER MB-HDS412



A



B







SPECIFICATIONS



Recommended excavator	ton	10 - 14
Weight	ton	1,2
Load capacity	m ³	0.55
Pressure	bar	230 - 280
Oil flow rate*	l/min	90 - 150
Size A	mm	1250
Size B	mm	1220
Size C	mm	1110

* The minimum hydraulic flow rate value must be alongside the required operating pressure.

SHAFT KIT

KIT	ADJUSTMENT*	APPLICATION
 RQ8 Sifting kit RQ20 Sifting kit RQ50 Sifting kit	8 mm 20 mm 50 mm	Sifting damp/dry soil Soil Aeration
 RM Mixer kit		Soil Aeration Compost Aeration Charcoal reduction Glass reduction Drywall reduction
 RE8 Fine sifting kit RE16 Fine sifting kit	8.5 mm 16 mm	Sifting damp/dry soil
 RC Compost kit	36.5 mm	Shredding foliage and small branches Composting

* Shafts in closed position.

OPTIONAL ACCESSORIES

RQ8 Sifting kit	RQ20 Sifting kit
RQ50 Sifting kit	RM Mixer kit
RE8 Fine sifting kit	RE16 Fine sifting kit
RC Compost kit	Shaft holder
24 Month Warranty	

APPLICATION AREAS



Road works



Tunnels



Enclosed spaces



Pipelines



Inert material recycling



Excavations



Urban construction sites



Foundries



Maintaining landscape and agricultural areas