

SHAFTS SCREENERS MB-HDS212









SPECIFICATIONS

\underline{O}	Recommended excavator	lb	11,020 - 22,050
	Recommended backhoe loader/loader*	lb	17,640 - 19,840**
6 ~	Recommended skid steer loader*	lb	6,610 - 8,820
	Weight		1,058
	Load capacity	СУ	0.20
	Pressure	PSI	2,901 - 3,626
	Oil flow rate***	gal/min	20 - 26
	Size A	in	48
	Size B	in	32
	Size C	in	28

* Please verify machine's Rated Operating Capacity

** Applicable only on the rear arm of the backhoe.

*** The minimum hydraulic flow rate value must be alongside the required operating pressure

SHAFT KIT

	KIT	ADJUSTMENT*	APPLICATION
	RQ8 Sifting kit RQ20 Sifting kit RQ50 Sifting kit	0.30 in 0.8 in 2.0 in	Sifting damp/dry soil Soil Aeration
(All all all all all all all all all all	RM Mixer kit		Soil Aeration Compost Aeration Charcoal reduction Glass reduction Drywall reduction
	RE8 Fine sifting kit RE16 Fine sifting kit	0.30 in 0.60 in	Sifting damp/dry soil
	DC Compost kit	1.40 in	Shredding foliage and small branches

1.40 in

* Shafts in closed position.

RC Compost kit

OPTIONAL ACCESSORIES

RQ8 Sifting kit	RQ20 Sifting kit	
RQ50 Sifting kit	RM Mixer kit	
RE8 Fine sifting kit	RE16 Fine sifting kit	
RC Compost kit	Shaft holder	

24 Month warranty

APPLICATION AREAS

Tunnels

site





r\$



Composting



Recycling aggregates

Urban construction Foundries

Maintaining landscape and agricultural areas



MBCRUSHER.COM

