
## **SHAFTS SCREENER**

# **MB-HDS323**





A





# **SPECIFICATIONS**



Recommended excavator	ton	22 - 35
Recommended backhoe loader/loader*	ton	12 - 16
Weight	ton	2,4
Load capacity	m³	1,65 - 2,00**
Load capacity with coal capacity increase kit	m³	2,00 - 2,40**
Pressure	bar	250 - 300
Oil flow rate***	l/min	120 - 160
Size A	mm	2330
Size B	mm	1500
Size C	mm	1250

<sup>\*</sup> Please verify machine's Rated Operating Capacity.

## **SHAFT KIT**

KIT

RQ8 Sifting kit RQ20 Sifting kit RQ50 Sifting kit	8 mm 20 mm 50 mm	Sifting damp/dry soil Soil Aeration
RM Mixer kit		Soil Aeration Compost Aeration Charcoal reduction Glass reduction Drywall reduction
RE8 Fine sifting kit RE16 Fine sifting kit	8.5 mm 16 mm	Sifting damp/dry soil
RC Compost kit	36.5 mm	Shredding foliage and small branches Composting

ADJUSTMENT\*

APPLICATION

## **OPTIONAL ACCESSORIES**

RQ8 Sifting kit	RQ20 Sifting kit
RQ50 Sifting kit	RM Mixer kit
RE8 Fine sifting kit	RE16 Fine sifting kit
RC Compost kit	Shaft holder
24 Month Warranty	

# **APPLICATION AREAS**









Inert material recycling





Urban construction

sites

Enclosed spaces

Foundries



Maintaining landscape and agricultural areas

<sup>\*\*</sup> The value of the load capacity varies according to the type of material being processed.

<sup>\*\*\*</sup> The minimum hydraulic flow rate value must be alongside the required operating pressure.

<sup>\*</sup> Shafts in closed position.