Card No TAN59-EN

Review of the01/06/2024



Aleatan COLORFIX L

COMPOSITION

Liquid solution based on condensed profisenitin tannin extracted from quebracho wood (Schinopsis Iorentii) stabilized at origin with SO2.

GENERAL CHARACTERISTICS

Aleatan COLORFIX L is a liquid tannin that is very active in color stabilization of red wines. Profisenitinic tannins are structurally very similar to the catechinic tannins naturally present in grapes and therefore are able to complement them effectively direct and via ethanal bridging stabilization of anthocyanins.

Aleatan COLORFIX L is therefore the ideal tannin for color stabilization of musts very rich in anthocyanins and with an imbalance in the T/A ratio also related to the specific production stage (beginning of maceration).

APPLICATIONS

Color stabilization in red wine making.

In pre-fermentation, starting from crushing, to filling the winemaker, to racking. Ideal for musts very rich in anthocyanins.

RECOMMENDED DOSAGES

Red wines beginning maceration 10 - 40 g/100 kg crushed Red wines racking: 5 - 10 g/hL Thermovinified and desulfurized wines: 5 - 30 g/hL

MODE OF USE

Dissolve in a small amount of water or must and add to the mass to be treated, homogenizing carefully.

PACKAGES AVAILABLE

Bottle 1 kg Bag in Box 10 kg Bag in Box 300 kg 20 kg canister Bag in Box 600 kg

STORAGE CONDITIONS

Unopened package: store in a cool (temperature below 25°C), dry and ventilated place.

Open package: close tightly and store as indicated above.

Protect from air and sunlight. In its original packaging, the product retains all its properties for 24 months.

Exclusively for oenological and professional use - Reg. (EU) 2022/68

Product obtained from raw materials in accordance with O.I.V. International Oenological Codex

Contains allergens: SO2

40062 Molinella (BO) - ITALIA
Tel. +39 051 88 7052
+39 346 58 33 882
info@alea-evolution.com
alea-evolution@pec.it
alea-evolution.com
CF - P.IVA 02944251202
Cod. REA BO-479327

Capitale sociale € 40.000,00 i.v.

Via Sandro Pertini, 12





The information given in this Technical Data Sheet corresponds to the current state of our knowledge and is subject to modification and supplementation without prior notice. The methods of use given do not relieve the user from the application and observance of safety and protection regulations. Adaptation to individual cases, as a consequence of the specific circumstances of each use, as well as possible misuse of the product, do not involve the responsibility of Alea Evolution S.R.L.