

Aleadet FLOOR

COMPOSITION

2-aminoethanol (Ethanalamine), ethoxylated alkyl alcohol (Trideceth-8), tetrasodium ethylenediaminetetraacetate (Tetrasodium EDTA).

GENERAL CHARACTERISTICS

ALEADEFLOOR encompasses in its formulation all the features to successfully solve many problems related not only to optimal removal of tenacious contamination, but also allows these operations to be carried out with complete safety for users.

ALEADEFLOOR, when applied at the recommended concentrations and temperature, is compatible with all types of materials commonly used in industry.

In the case of uncertainty, the individual material should be evaluated before prolonged contact.

APPLICATIONS

ALEADEFLOOR can be used in all areas of the food and wine industry.

RECOMMENDED DOSAGES

ALEADEFLOOR is used at a concentration ranging from 10 percent in water.

MODE OF USE

It is recommended to dilute ALEADEFLOOR directly in water or use pure depending on the nature of the residues to be removed. Rinse thoroughly after use.

Refer to the MSDS for information on handling and storage of the product.

PACKAGES AVAILABLE

10 kg canister

STORAGE CONDITIONS

Unopened package: store in a cool (temperature below 25°C), dry and ventilated place.

Open package: close tightly and store as indicated above.



ALEA
Evolution

Via Sandro Pertini, 12
40062 Molinella (BO) - ITALIA
Tel. +39 051 88 7052
+39 346 58 33 882
info@alea-evolution.com
alea-evolution@pec.it
alea-evolution.com
CF - P.IVA 02944251202
Cod. REA BO-479327
Capitale sociale € 40.000,00 i.v.

