

SHAFTS SCREENERS

MB-HDS312









SPECIFICATIONS



Recommended excavator	ton	/ -]]
Weight	ton	0,72
Load capacity	m³	0.35
Pressure	bar	200 - 250
Oil flow rate*	I/min	75 - 100
Size A	mm	1235
Size B	mm	985
Size C	mm	880

^{*} The minimum hydraulic flow rate value must be alongside the required operating pressure

SHAFT KIT

	KIT	ADJUSTMENT*	APPLICATION
	RQ8 Sifting kit RQ20 Sifting kit RQ50 Sifting kit	8 mm 20 mm 50 mm	Sifting damp/dry soil Soil Aeration
	RM Mixer kit		Soil Aeration Compost Aeration Charcoal reduction Glass reduction Drywall reduction
C	RE8 Fine sifting kit RE16 Fine sifting kit	8.5 mm 16 mm	Sifting damp/dry soil
	RC Compost kit	36.5 mm	Shredding foliage and small branches Composting

^{*} Shafts in closed position.

OPTIONAL ACCESSORIES

RQ8 Sifting kit	RQ20 Sifting kit	
RQ50 Sifting kit	RM Mixer kit	
RE8 Fine sifting kit	RE16 Fine sifting kit	
RC Compost kit	Shaft holder	

APPLICATION AREAS













Urban construction site



Foundries

Maintaining landscape and agricultural areas

Rev. 20240926