## SHAFTS SCREENERS **MB-HDS312**





4

Recommended excavator	lb	15,430 - 24,250
Weight	lb	1,587
Load capacity	СУ	0.46
Pressure	PSI	2,901 - 3,626
Oil flow rate*	gal/min	20 - 26
Size A	in	49
Size B	in	39
Size C	in	35

\* The minimum hydraulic flow rate value must be alongside the required operating pressure

## **SHAFT KIT**

КІТ	ADJUSTMENT*	APPLICATION
RQ8 Sifting kit RQ20 Sifting kit RQ50 Sifting kit	0.30 in 0.8 in 2.0 in	Sifting damp/dry soil Soil Aeration
RM Mixer kit		Soil Aeration Compost Aeration Charcoal reduction Glass reduction Drywall reduction
RE8 Fine sifting kit RE16 Fine sifting kit	0.30 in 0.60 in	Sifting damp/dry soil
RC Compost kit	1.40 in	Shredding foliage and small branches Composting

\* Shafts in closed position.

## **OPTIONAL ACCESSORIES**

RQ8 Sifting kit	RQ20 Sifting kit	
RQ50 Sifting kit	RM Mixer kit	
RE8 Fine sifting kit	RE16 Fine sifting kit	
RC Compost kit	Shaft holder	
24 Month warranty		

## **APPLICATION AREAS**








Recycling aggregates

Maintaining landscape and agricultural areas

oelines E



A

The data and images provided above are not binding, as the manufacturer reserves the right to make improvements to its products at any time and without notice.