

SHAFTS SCREENERS MB-HDS320









SPECIFICATIONS

Recommended excavator	ton	18 - 24
Recommended backhoe loader/loader*	ton	11 - 14
Weight	ton	2,1
Load capacity		1,35
Pressure	bar	250 - 300
Oil flow rate**	l/min	120 - 160
Size A	mm	2050
Size B	mm	1350
Size C	mm	1250

* Please verify machine's Rated Operating Capacity

** The minimum hydraulic flow rate value must be alongside the required operating pressure

SHAFT KIT

KIT	ADJUSTMENT*	APPLICATION
RQ8 Sifting kit RQ20 Sifting kit RQ50 Sifting kit	8 mm 20 mm 50 mm	Sifting damp/dry soil Soil Aeration
RM Mixer kit		Soil Aeration Compost Aeration Charcoal reduction Glass reduction Drywall reduction
RE8 Fine sifting kit RE16 Fine sifting kit	8.5 mm 16 mm	Sifting damp/dry soil
RC Compost kit	36.5 mm	Shredding foliage and small branches Composting

* Shafts in closed position.

OPTIONAL ACCESSORIES

RQ8 Sifting kit	RQ20 Sifting kit	
RQ50 Sifting kit	RM Mixer kit	
RE8 Fine sifting kit	RE16 Fine sifting kit	
RC Compost kit	Shaft holder	

24 Month warranty

APPLICATION AREAS



Pipelines



Quarrv

54 Recycling aggregates



Excavations



Urban construction

site



15 Foundries



Maintaining landscape and agricultural areas

